

US009636019B2

(12) United States Patent Hendler et al.

(54) DEVICE FOR USE IN ELECTRO-BIOLOGICAL SIGNAL MEASUREMENT IN THE PRESENCE OF A MAGNETIC FIELD

(75) Inventors: Talma Hendler, Tel Aviv (IL);

Mordekhay Medvedovsky, Beer-Sheva (IL); Andrey Zhdanov, Helsinki (FI); Ilana Klovatch, Petah Tikva (IL); Firas

Fahoum, Tel Aviv (IL)

(73) Assignee: THE MEDICAL RESEARCH, INFRASTRUCTURE, AND HEALTH

SERVICES FUND OF THE

TEL-AVIV MEDICAL CENTER, Tel

Aviv (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 693 days.

(21) Appl. No.: 13/878,297

(22) PCT Filed: Oct. 6, 2011

(86) PCT No.: **PCT/IL2011/000785**

§ 371 (c)(1),

(2), (4) Date: Apr. 8, 2013

(87) PCT Pub. No.: **WO2012/046237**

PCT Pub. Date: Apr. 12, 2012

(65) Prior Publication Data

US 2013/0204122 A1 Aug. 8, 2013

Related U.S. Application Data

- (60) Provisional application No. 61/390,722, filed on Oct. 7, 2010, provisional application No. 61/445,080, filed on Feb. 22, 2011.
- (51) **Int. Cl.**A61B 5/05 (2006.01)

 A61B 5/00 (2006.01)

 (Continued)

(10) Patent No.: US 9,636,019 B2

(45) **Date of Patent:**

May 2, 2017

2562/222 (2013.01)

(52) U.S. Cl. CPC A61B 5/0055 (2013.01); A61B 5/0476 (2013.01); A61B 5/0478 (2013.01); A61B

(58) Field of Classification Search

CPC A61B 2562/222; A61B 5/0055; A61B 5/0476; A61B 5/0478

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,998,213 A	*	12/1976	Price	A61B 5/0424
5,479,934 A	*	1/1996	Imran	600/383 A61B 5/0017
				600/390

(Continued)

FOREIGN PATENT DOCUMENTS

WO 99/22642 A1 5/1999

OTHER PUBLICATIONS

Srivastava et al. "ICA-based procedures for removing ballistocardiogram artifacts from EEG data acquired in the MRI scanner." NeuroImage 24 (2005), 50-60.*

(Continued)

Primary Examiner — Jonathan Cwern Assistant Examiner — Amelie R Gillman (74) Attorney, Agent, or Firm — Browdy and Neimark, PLLC

(57) ABSTRACT

A device is presented for use in an EEG measurement performed in the presence of a magnetic field. The device includes a wiring array for connecting an electrodes arrangement to an electroencephalogram (EEG) monitoring device. The wiring array includes sampling lines arranged to form first and second groups of sampling lines, arranged in a spaced-apart substantially parallel relationship extending along first and second axes respectively, at least some of the (Continued)

